

Catalys® Optimum Full Synthetic 5W40

DESCRIPTION

Optimum Full Synthetic SAE 5W40 is a premium full synthetic engine oil formulated to meet and exceed the stringent high-performance requirements of European passenger car and light-duty diesel vehicles. Formulated with state-of-the-art base stocks and high-performance additives, **Optimum Full Synthetic SAE 5W40** is designed to provide the highest level of engine protection available, even under the most severe operating conditions.

APPLICATION / BENEFITS

Catalys Optimum Full Synthetic 5W40 provides the following features and benefits:

- Excellent oxidation stability
- Excellent shear stability
- Easy start at low temperatures
- Reduces formation of sludge and varnish deposits
- Exceptional wear protection for all engine parts

This lubricant meets the requirements of the following specifications: API SN, VW 502 00/ 505 00/505 01, Porsche A40, ACEA C3, BMW Longlife-04 Oil and MB 229.31/ 229.51

PHYSICAL PROPERTIES	ASTM METHOD	Optimum Full Synthetic 5W40
Kinematic Viscosity at 40°C, cSt	D445	85,5
Kinematic Viscosity at 100°C, cSt, per SAE std	D445	13,9
Viscosity Index	D2270	168
Density at 15°C, kg/L	D1298	0,856
Pour Point, (°C)	D97	-45
NOACK Volatility, 250°C, evaporation loss, 1h, (%)		9
Dynamic Viscosity (CCS), °C/mPa.s, max	D5293	(-30/6600 max) 6000 typ.

The values listed above are typical of current production, variations in these properties may occur.

AVAILABLE PACK SIZES

	Bulk	Drum	4 X 5L
Catalys Optimum Full Synthetic 5W40	07-3504-00	07-3504-05	07-3504-35

THE PACK SIZES ABOVE ARE OUR STANDARD PACK SIZES. PLEASE COMMUNICATE WITH US TO FIND OUT FORMATS AVAILABLE LOCALLY.

HEALTH / SAFETY

GHS compliant English and French Safety Data Sheets are available at catalyslubricants.ca under 'Safety Data Sheets'. Keep container closed when not in use. Please refer to the SDS for safe handling information. Always take used oil and containers to an authorized collection point. Avoid discharge into the environment. As with any oil, keep out of reach of children and animals.

QUALITY

Catalys Lubricants partners with respected industry suppliers to bring you high quality products. For more information, contact your local Catalys Representative. Please ensure this product is right for the equipment by following the recommendations of the equipment operating manual.

CONTACT US

British Columbia	Alberta	Manitoba	Ontario	Quebec
7483 Progress Way Delta, BC	Unit 130, 16815 117 th Ave NW Edmonton, AB	25 Midland Street Winnipeg, MB	3462 White Oak Road London, ON	2320, rue de la Métropole Longueuil, QC
V4G 1E7 855.946.4226	T5M 3V6 877.222.8507	R3E 3J6 855.755.6737	N6E 2Z9 800.673.6231	J4G 1E6 800.363.0590

Catalys® is a registered trademark of Entreprises Émile Crevier Inc.